# Bohnenkamp Moving Professionals

**TYRES** 

Product group	Tyres	
Item number	10000688	
Valid tyre size	710 / 70 R 42	
LI / SI / PR	176 A8 / 173 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Agrimax Factor	





#### Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial . tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride • comfort.
- The reduced lug angle allows for reduced rolling . resistance.
- The large contact area ensures smooth running. •
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

## **Technical Informations**

ien number10000688EAN80309070159Vald yre size10/07 R4L/SI / PR10/80 A1030Brad10/80 A1030Brad8/80 A1030Tard pattern8/80 A1030Craos properies8/80 A1030Bradsconce8/80 A1030Type of an antice8/80 A1030Type of antice8/80 A1030Type of antice8/80 A1030Bradsconce8/80 A1030Bradsconce8/80 A1030Bradsconce8/80 A1030Bradsconce9/80 A1030Brads		
Vald yre sizeVald yre size707 R 42107 R 4276 A6 173 DL 1 / S 1 / S 176 A6 173 DTrad1Brand8 TBrand8 TCarcas properiesE ReadyJ 2 Arads8 NTre colur10 ABrand10 ATre colur10 ABrand10 ATre colur10 ABrand10 ATre colur10 ABrand10 ABrand Brand10 ABrand Brand10 ABrand Brand10 ABrand Brand10 ABrand Brand10 ABrand Brand Brand10 ABrand Brand B	Item number	10000688
LI/SI/PR768/173 DLI/SI/PR768/173 DLI/TLFandKTBrandKTTread patternAiniax EatorArtasticReadyBackStTre colourBackBackStKetogewicht [kg] (bg)St.85Pernited rin sizeJ02Artaniani pressure [b]St.96Steion vidth (m)St.96Stein vidth (m)St.96 <th>EAN</th> <th>8903094070169</th>	EAN	8903094070169
TLTTTI.TLTTTI.FradBKT.BradArimax FactorTread patternAirimax FactorCacass propertiesE-ReadyAntstaticNoTyre colourBickTore colourE-CE 106Ketogewich [tig] (tig)21.85Pentied rin sizeDV23Aristing colourJ.Aristing colourJ.Aristing colourJ.Aristing colourJ.Pentied rin sizeJ.J.J.Stating colourJ.Aristing colour	Valid tyre size	710 / 70 R 42
BrandBKTBrandBKTFread patternAgimax FactorCacass propertiesE-ReadyAnistaticNoTyre colurBlackEC regulation numberBlackBreadyDivasRecommended rin sizeDivasMaximum air pressure DataJacaArating functionStandamTerd vid functionStandamBreadwidt (Ng)JacaBreadwidt (Ng)Jaca	LI / SI / PR	176 A8 / 173 D
Tead patternAprimas FactorTead patternAprimas FactorCarcass propertiesE-ReadyAntistaticNoTyre colourBackECE regulation numberECE 106Nettogewicht [kg] (gül igg)21.85Paemited rim sizeDW258Maximum air pressure [kg]24.0Steton width (mm)51.6Out of damas factor76.0Steton width (mm)90.5Stat radius (SLR) [mm]90.5Stat radius (SLR) [mm]91.5Stat dapter forty6.0Stat	TL/TT	т
Carcass propertiesE-ReadyCarcass propertiesE-ReadyAnistaticNoAnistaticSolaTyre colourBlackECE regulation numberECE 106Actogewicht [kg] (giltig)321.85Recommended rim sizeDW23BPermitted rim sizeSoleAximum air pressure [bas]2.40Section width (mm)16Outer diameter of tyre [mm]305Stat. radius (SLR) [mm]305Reding include (SLR) [mm]50.9Reding include (SLR) [mm]50.9Autometer of tyre [mm]50.9Autometer of tyre [mm]50.9Autometer of tyre [mm]50.9Stat. radius (SLR) [mm]50.9Suble (SLR) [mm]50.9Autometer of tyre [mm]50.9Autometer of tyre [mm]50.9Suble (SLR) [mm]50.9Suble (	Brand	ВКТ
AnistaticNoAnistaticNoTyre colourBlackECE regulation numberECE 106Nettogewicht [kg] (giltig)31.85Recommended rim sizeDW28BPernitted rim sizeDW25BSation width (mm)1.40Section width (mm)0.50Outer diameter of type (mm)30.90Stat. radius (SLR) [mm]30.90Apilog Circumference (mm)5.90Rolling circumference (mm)5.90Subsch (mm)5.90Subsch (mm)3.90Stat. radius (SLR) [mm]3.90Subsch (mm)S.90Subsch (mm)	Tread pattern	Agrimax Factor
Tyre colourBakaFCE regulation numberECE 106Nettogewicht [kg] (ülitig)2018Recommended rin sizeDW28Permitted rin sizeDW28Ausinum air pressure [bas]2.40Section width (mm)3.6Tead width (mm)0.61Star adius (SLR) [mm]3.9Speed Radius Index (SR)3.9Frand regulation (SLR) [mm]3.9Tead optin (mm)3.9Speed Radius Index (SR)3.9Tead optin (mm)3.9Speed Radius Index (SR)3.9Speed Radius Index (SR)3.9	Carcass properties	E-Ready
FCE regulation numberECE 106Bettogewicht [kg] (gillig)S21.85Recommended rim sizeDW23BPermitted rim sizeDW25BMaximunair pressure [ba]2.40Section width (mm)10Otage and the function of the fu	Antistatic	No
Nettogewicht [kg] (tjültig)32.185Recommended rim sizeDW23BPermitted rim sizeDW25BMaximum air pressure [ba]2.40Section widht (mm)16Otage and widht (mm)0.50Outer diameter of tyre [mm]0.91Stat. radius (SLR) [mm]9.50Speed Radius Index (STR)0.50Rolling circumfer commenter5.90Number of Luga1.20Number of Luga1.20Subsciele Commenter1.20Subsciele Commenter1.20 <th< th=""><th>Tyre colour</th><th>Black</th></th<>	Tyre colour	Black
Recommended rim sizeDW238Pernitted rim sizeDW258Maxinum air pressure [bar]2.40Section width (mm)016Tead width (mm)0.50Otder diameter of tyre [mm]0.91Stat. radius (SLR) [mm]0.91Speed Radius Index (STR)0.91Tead depth (mm)0.91Signed Radius Index (SLR)0.91Tead depth (mm)0.91Diameter of tyre [mm]0.91Signed Radius Index (SLR)0.91Tead depth (mm)0.91Signed Radius Index (SLR)0.91Tead depth (mm)0.91Signed Radius Index (SLR)0.91Signed Radius Index (SLR)0.91Tead depth (mm)0.91Signed Radius Index (SLR)0.91Signed Radius Index (SLR)0.91 </th <th>ECE regulation number</th> <th>ECE 106</th>	ECE regulation number	ECE 106
Permitted rim sizeDW25BMaximum air pressure [ba]2,40Section width (mm)716Tread width (mm)675Outer diameter of tyre [mm]936Stat. radius (SLR) [mm]935Speed Radius Index (SR)75Rolling circumference [mm]5,00Tread depth (mm)12,20Bunber of lugs12,20	Nettogewicht [kg] (gültig)	321,85
Maximum air pressure [bar]2,40Section width (mm)716Tread width (mm)675Outer diameter of tyre [mm]2061Stat. radius (SLR) [mm]935Speed Radius Index (SRI)975Rolling circumference [mm]51,000Tread depth (mm)52,000Jumber of lugs12,200	Recommended rim size	DW23B
Section width (mm)1iaTread width (mm)675Outer diameter of tyre [m]0aiStat. radius (SLR) [m]935Speed Radius Index (SR)75Rolling circumference [m]5iaSalo1aiNumber of lugs1ai	Permitted rim size	DW25B
Tread width (mm)675Outer diameter of tyre [m]2061Stat. radius (SLR) [m]935Speed Radius Index (SR)975Rolling circumference [m]6198Tread depth (mm)80.Jumber of lugs1212	Maximum air pressure [bar].	2,40
Outer diameter of tyre [mm]2061Stat. radius (SLR) [mm]395Speed Radius Index (SRI)975Rolling circumference [mm]6198Tread depth (mm)58,0Number of lugs2122	Section width (mm)	716
Stat. radius (SLR) [mm]   935     Speed Radius Index (SRI)   975     Rolling circumference [mm]   6198     Tread depth (mm)   58,0     Number of lugs   2122	Tread width (mm)	675
Speed Radius Index (SRI) 975   Rolling circumference [mm] 6198   Tread depth (mm) 58,0   Number of lugs 21x2	Outer diameter of tyre [mm].	2061
Rolling circumference [mm] 6198   Tread depth (mm) 58,0   Number of lugs 21x2	Stat. radius (SLR) [mm]	935
Tread depth (mm)     58,0       Number of lugs     21x2	Speed Radius Index (SRI)	975
Number of lugs 21x2	Rolling circumference [mm].	6198
	Tread depth (mm)	58,0
	Number of lugs	21x2
E-Ready Yes	E-Ready	Yes

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		2,40	
173 D	6500	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.