Bohnenkamp Moving Professionals

RIMS

Product group	Rims
Item number	10000696
Valid rim size	DW 25 B x 26
Rim connection	12/371/425
Bolt hole design	A3
Offset (mm)	-70
Rim colour	Anthrazit
Brand	Jantsa





Technical Informations Load capacity of rim 1 [kg] 7300 Speed Rims 1 [km/h] 40 Load capacity of rim 2 [kg] 6100 Speed Rims 2 [km/h] 50 Maximum speed [km/h]. 50 Type of drive Towed axle Nettogewicht [kg] (gültig) 104,00 Hump kein Hump Valve protection VSH Single / multi-part einteilig **Rim material** steel

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

RAL	RAL7016
Cavity Sealed	No
Disc thickness [mm]	15
Verschweißung beidseitig	No
Ventilation holes	No
Number of bolt holes	12
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	371
Bolt hole circle diameter [mm]	425
Valve seat	External Valve
Valve hole diameter [mm]	15.7
	Na
Preassembled valve	No

14.03.2025