

## **TYRES**

Product group	Tyres
Item number	10000704
Valid tyre size	800 / 70 R 38
LI / SI / PR	173 D / 176 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Sonderpostenkategorie	Disassambled
type of damage	Dismounted



Mitas

## Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp
- Its big contact area provides excellent traction
- The flexible sidewalls enable high load capacities even at low inflation pressure



## **Technical Informations**

Item number	10000704
EAN	4040658106286
Valid tyre size	800 / 70 R 38
LI / SI / PR	173 D / 176 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	373,00
Permitted rim size	DW25B, DW27B
Maximum air pressure [bar].	1,60
Outer diameter of tyre [mm].	2052
Stat. radius (SLR) [mm]	911
Rolling circumference [mm].	6090
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		1,60	
176 A8	7100	40		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.