Bohnenkamp Moving Professionals

13.03.2025

TYRES

Product group	Tyres
Item number	10000706
Valid tyre size	320 / 90 R 50
LI / SI / PR	148 D
TL/TT	TL
Brand	Goodyear
Tread pattern	OPTITRAC
Sonderpostenkategorie	Disassambled
type of damage	Dismounted,Hole in the flank

Technical Informations

Item number	10000706
EAN	4040658106309
Valid tyre size	320 / 90 R 50
LI / SI / PR	148 D
TL/TT	TL
Brand	Goodyear
Tread pattern	OPTITRAC
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	124,00
Recommended rim size	10

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Maximum air pressure [bar].	3,20
Section width (mm)	310
Outer diameter of tyre [mm].	1864
Stat. radius (SLR) [mm]	876
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5716
Tread depth (mm)	41,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 D	3150	65		3,20	