Bohnenkamp Moving Professionals

13.03.2025

TYRES

Product group	Tyres
Item number	10000712
Valid tyre size	480 / 70 R 34
LI / SI / PR	155 D
TL/TT	TL
Brand	Goodyear
Tread pattern	OPTITRAC
Sonderpostenkategorie	Disassambled
type of damage	Dismounted

Technical Informations

Item number	10000712
EAN	4040658106361
Valid tyre size	480 / 70 R 34
LI / SI / PR	155 D
TL/TT	TL
Brand	Goodyear
Tread pattern	OPTITRAC
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	157,00
Recommended rim size	W15L

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Permitted rim size	W16L, W15A, W16A, DW16A
Maximum air pressure [bar].	3,20
Section width (mm)	481
Outer diameter of tyre [mm].	1584
Stat. radius (SLR) [mm]	732
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4826
Tread depth (mm)	51,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 D	3875	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.