

TYRES

Product group	Tyres
Item number	10000727
Valid tyre size	VF 800/ 70 R 38
LI / SI / PR	193 B
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Sonderpostenkategorie	Disassambled
type of damage	Dismounted



Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.



Technical Informations

Item number	10000727
EAN	4040658106521
Valid tyre size	VF 800/ 70 R 38
LI / SI / PR	193 B
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	370,00
Section width (mm)	794
Outer diameter of tyre [mm].	2085
Stat. radius (SLR) [mm]	902
Rolling circumference [mm].	6223
Tread depth (mm)	61,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
193 B	11500	50			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.