

WHEELS

Product group	Wheels
Item number	10000740
Valid wheel size	460 / 70 R 24
Brand	Alliance
Tread pattern	585
Valid rim size	DW 15 L x 24
Rim connection	10/281/335
Bolt hole design	B3
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15235226
LI / SI / PR	159 A8 / 159 B
Load capacity 1 [kg]	4375
Speed 1 [km/h].	40
Load capacity 2 [kg]	4375
Speed 2 [km/h].	50
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	198,75
ECE regulation number	ECE 106

Section width (mm)	471
Stat. radius (SLR) [mm]	560
Rolling circumference [mm].	3704
Tread depth (mm)	35,0
Number of lugs	24x2
E-Ready	No
Assembly Item no. Rim	• 10000778
Load capacity of rim 1 [kg]	5750
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4850
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,00
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
Rim colour (manufacturer's designation)	Fendt Terra - red
Cavity Sealed	No
Disc thickness [mm]	12
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27

Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade