

TYRES

Product group	Tyres
Item number	10000744
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2 / 193 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS302



MAXAM

Notes and features

- The Maxam MS302 is an EM radial tyre for use on wheel loaders and dumpers.
- Its tread pattern provides very good traction in all off-road conditions.
- A thick undertread and the wear and cut resistant tread compound provide good protection against damage.
- The increased net-to-gross and the large tread depth guarantee a long service life.
- The reinforced tread blocks minimise vibrations at transport speeds.

Technical Informations

Item number	10000744
EAN	6959655431018
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2 / 193 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS302
TRA Code	E3/L3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	449,00
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	6,50
Section width (mm)	673
Outer diameter of tyre [mm].	1742
Stat. radius (SLR) [mm]	784
Rolling circumference [mm].	5197
Tread depth (mm)	40,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 A2	18500	10	Loader dozer	6,50	
193 B	11500	50	Transport	5,25	