

TYRES

Product group	Tyres
Item number	10000746
Valid tyre size	650 / 65 R 25
LI / SI / PR	200 A2 / 180 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS302





Notes and features

- The Maxam MS302 is an EM radial tyre for use on wheel loaders and dumpers.
- Its tread pattern provides very good traction in all off-road conditions.
- A thick undertread and the wear and cut resistant tread compound provide good protection against damage.
- The increased net-to-gross and the large tread depth guarantee a long service life.
- The reinforced tread blocks minimise vibrations at transport speeds.



Technical Informations

Item number	10000746
EAN	6959655443301
Valid tyre size	650 / 65 R 25
LI / SI / PR	200 A2 / 180 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS302
TRA Code	E3/L3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	314,00
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	6,25
Section width (mm)	636
Outer diameter of tyre [mm].	1479
Stat. radius (SLR) [mm]	619
Tread depth (mm)	37,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
200 A2	14000	10	Loader dozer	6,25	
180 B	8000	50	Transport	4,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.