

TYRES

Product group	Tyres
Item number	10000747
Valid tyre size	29.5 R 25
LI / SI / PR	216 A2 / 200 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS302



MAXAM

Notes and features

- The Maxam MS302 is an EM radial tyre for use on wheel loaders and dumpers.
- Its tread pattern provides very good traction in all off-road conditions.
- A thick undertread and the wear and cut resistant tread compound provide good protection against damage.
- The increased net-to-gross and the large tread depth guarantee a long service life.
- The reinforced tread blocks minimise vibrations at transport speeds.

Technical Informations

Item number	10000747
EAN	6959655431049
Valid tyre size	29.5 R 25
LI / SI / PR	216 A2 / 200 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS302
TRA Code	E3/L3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	590,00
Recommended rim size	25.00/3.5
Maximum air pressure [bar].	6,50
Section width (mm)	747
Outer diameter of tyre [mm].	1881
Stat. radius (SLR) [mm]	840
Rolling circumference [mm].	5590
Tread depth (mm)	42,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
216 A2	22400	10	Loader dozer	6,50	
200 B	14000	50	Transport	5,25	