

## **TYRES**

Product group	Tyres
Item number	10000748
Valid tyre size	550 / 65 R 25
LI / SI / PR	182 A2 / 172 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS302





## Notes and features

- The Maxam MS302 is an EM radial tyre for use on wheel loaders and dumpers.
- Its tread pattern provides very good traction in all off-road conditions.
- A thick undertread and the wear and cut resistant tread compound provide good protection against damage.
- The increased net-to-gross and the large tread depth guarantee a long service life.
- The reinforced tread blocks minimise vibrations at transport speeds.



## **Technical Informations**

Item number	10000748
EAN	6959655473377
Valid tyre size	550 / 65 R 25
LI / SI / PR	182 A2 / 172 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS302
TRA Code	E3/L3
Star Rating	*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	232,00
Recommended rim size	17.00/2.0
Maximum air pressure [bar].	4,75
Section width (mm)	547
Outer diameter of tyre [mm].	1347
Stat. radius (SLR) [mm]	593
Tread depth (mm)	35,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
182 A2	8500	10	Loader dozer	4,75	
172 B	6300	50	Transport	4,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.