

TYRES

Product group	Tyres
Item number	10000749
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2
TL/TT	TL
Brand	Maxam
Tread pattern	MS502 MINEXTRA



Notes and features

- The Maxam MS502 MineXtra is an EM radial tyre for wheel loaders and vehicles in the toughest applications.
- Its closed tread with extra high tread depth of L5S is particularly resistant to abrasion and cuts.
- The deep undertread increases puncture resistance.
- The reinforced tyre bead, tyre shoulder and sidewall also provide extra durability.

Technical Informations

Item number	10000749
EAN	6959655425628
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2
TL/TT	TL
Brand	Maxam
Tread pattern	MS502 MINEXTRA
TRA Code	L5S
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	783,00
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	6,50
Section width (mm)	675
Outer diameter of tyre [mm].	1796
Stat. radius (SLR) [mm]	805
Rolling circumference [mm].	5347
Tread depth (mm)	96,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 A2	18500	10	Loader dozer	6,50	