

## **TYRES**

Product group	Tyres
Item number	10000751
Valid tyre size	17.5 R 25
LI / SI / PR	182 A2
TL/TT	TL
Brand	Maxam
Tread pattern	MS502 MINEXTRA





## Notes and features

- The Maxam MS502 MineXtra is an EM radial tyre for wheel loaders and vehicles in the toughest applications.
- Its closed tread with extra high tread depth of L5S is particularly resistant to abrasion and cuts.
- The deep undertread increases puncture resistance.
- The reinforced tyre bead, tyre shoulder and sidewall also provide extra durability.



## **Technical Informations**

Item number	10000751
EAN	6959655425284
Valid tyre size	17.5 R 25
LI / SI / PR	182 A2
TL/TT	TL
Brand	Maxam
Tread pattern	MS502 MINEXTRA
TRA Code	L5S
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	286,00
Recommended rim size	14.00/1.5
Maximum air pressure [bar].	6,50
Section width (mm)	433
Outer diameter of tyre [mm].	1408
Stat. radius (SLR) [mm]	647
Rolling circumference [mm].	4242
Tread depth (mm)	72,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
182 A2	8500	10		6,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.