

TYRES

Product group	Tyres
Item number	10000752
Valid tyre size	29.5 R 25
LI / SI / PR	216 A2 / 200 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS405 DUMPXTRA





Notes and features

- The Maxam MS405 DUMPXTRA is an EM radial tyre for articulated dumpers and wheel loaders in various applications.
- Its low profile (E4/L4) provides excellent traction in all offroad conditions.
- The thick base layer and the cut and wear-resistant rubber compound protect the tyre from damage and guarantee good durability.
- The wide and flat contact surface provides stability and ensures slow, uniform wear.



Technical Informations

Item number	10000752
EAN	6959655438932
Valid tyre size	29.5 R 25
LI / SI / PR	216 A2 / 200 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS405 DUMPXTRA
TRA Code	E4/L4
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	630,00
Recommended rim size	25.00/3.5
Maximum air pressure [bar].	6,50
Section width (mm)	755
Outer diameter of tyre [mm].	1872
Stat. radius (SLR) [mm]	845
Rolling circumference [mm].	5592
Tread depth (mm)	63,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
216 A2	22400	10	Loader dozer	6,50	
200 B	14000	50	Transport	5,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.