

TYRES

Product group	Tyres
Item number	10000753
Valid tyre size	750 / 65 R 25
LI / SI / PR	209 A2 / 190 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS302



MAXAM

Notes and features

- The Maxam MS302 is an EM radial tyre for use on wheel loaders and dumpers.
- Its tread pattern provides very good traction in all off-road conditions.
- A thick undertread and the wear and cut resistant tread compound provide good protection against damage.
- The increased net-to-gross and the large tread depth guarantee a long service life.
- The reinforced tread blocks minimise vibrations at transport speeds.

Technical Informations

Item number	10000753
EAN	6959655443295
Valid tyre size	750 / 65 R 25
LI / SI / PR	209 A2 / 190 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS302
TRA Code	E3/L3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	461,00
Recommended rim size	24.00/3.0
Maximum air pressure [bar].	6,50
Section width (mm)	744
Outer diameter of tyre [mm].	1596
Stat. radius (SLR) [mm]	664
Tread depth (mm)	41,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 A2	18500	10	Loader dozer	6,50	
190 B	10600	50	Transport	5,25	