

WHEELS

Product group	Wheels
Item number	10000756
Valid wheel size	800 / 35 - 22.5
Brand	Alliance
Tread pattern	128
Valid rim size	AG 28.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-75
Rim colour	Silver
Load capacity complete wheel [kg]	4750
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15212674
LI / SI / PR	169 A8 / 162 D, 16 PR
Load capacity 1 [kg]	5800
Speed 1 [km/h].	40
Load capacity 2 [kg]	4750
Speed 2 [km/h].	65
Direction	Left
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	221,83
ECE regulation number	ECE 106

Section width (mm)	800
Stat. radius (SLR) [mm]	523
Rolling circumference [mm].	3508
Tread depth (mm)	26,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	325
E-Ready	No
Assembly Item no. Rim	• 33060459
Load capacity of rim 1 [kg]	7600
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5600
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,60
Type of drive	Towed axle
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27

Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade