

## WHEELS

Product group	Wheels
Item number	10000768
Valid wheel size	15.0 / 55 - 17
Brand	BKT
Tread pattern	AS 504
Valid rim size	13.00 X 17
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	-54
Rim colour	Silver
Load capacity complete wheel [kg]	2575
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15711865
LI / SI / PR	128 A8 / 141 A8, 14 PR
Load capacity 1 [kg]	1800
Speed 1 [km/h].	40
Load capacity 2 [kg]	2575
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	60,49
ECE regulation number	ECE 106
Section width (mm)	380

Stat. radius (SLR) [mm]	395
Rolling circumference [mm].	2608
Tread depth (mm)	23,0
Number of lugs	17x2
E-Ready	No
Assembly Item no. Rim	• 33060117
Load capacity of rim 1 [kg]	3800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2800
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,70
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve

---

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade