

## **RIMS**

Product group	Rims
Item number	10000778
Valid rim size	DW 15 L x 24
Rim connection	10/281/335
Bolt hole design	В3
Brand	Jantsa





Technical Informations		
Load capacity of rim 1 [kg]	5750	
Speed Rims 1 [km/h]	25	
Load capacity of rim 2 [kg]	4850	
Speed Rims 2 [km/h]	40	
Maximum speed [km/h].	40	
Type of drive	Towed axle	
Nettogewicht [kg] (gültig)	95,00	
Hump	kein Hump	
Valve protection	VSH	
Single / multi-part	einteilig	
Rim material	steel	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rim colour (manufacturer's designation)	Fendt Terra - red
Cavity Sealed	No
Disc thickness [mm]	12
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No