

TYRES

Product group	Tyres
Item number	10000799
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2 / 193 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS300



Notes and features

- The Maxam MS300 is an EM tire for wheel loaders, dumpers, graders and similar vehicles.
- It is ideal for use on sandy or simple surfaces.
- The tyre provides very good traction even when working off-road.
- Its thick base rubber layer and the cut and wear-resistant rubber compound provide very good protection against injuries.

Technical Informations

Item number	10000799
EAN	6959655430998
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2 / 193 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS300
TRA Code	E3/L3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	462,00
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	6,50
Section width (mm)	669
Outer diameter of tyre [mm].	1739
Stat. radius (SLR) [mm]	751
Tread depth (mm)	35,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 A2	18500	10	Loader dozer	6,50	
193 B	11500	50	Transport	5,25	