

TYRES

Product group	Tyres
Item number	10000799
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2 / 193 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS300





Notes and features

- The Maxam MS300 is an EM tire for wheel loaders, dumpers, graders and similar vehicles.
- It is ideal for use on sandy or simple surfaces.
- The tyre provides very good traction even when working off-road
- Its thick base rubber layer and the cut and wear-resistant rubber compound provide very good protection against injuries.



Technical Informations

Item number	10000799
EAN	6959655430998
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2 / 193 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS300
TRA Code	E3/L3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	462,00
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	6,50
Section width (mm)	669
Outer diameter of tyre [mm].	1739
Stat. radius (SLR) [mm]	751
Tread depth (mm)	35,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 A2	18500	10	Loader dozer	6,50	
193 B	11500	50	Transport	5,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.