Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres
Item number	10000803
Valid tyre size	335 / 80 R 18
LI / SI / PR	145 A2 / 134 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS910R





Notes and features

- The Maxam MS910R is a radial tyre for wheel loaders and telescopic loaders.
- Its versatile tread offers particularly good traction on muddy surfaces.
- The reinforced sidewall protects the tyre and rim from damage.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10000803
	1000803
EAN	6959655435146
Valid tyre size	335 / 80 R 18
LI / SI / PR	145 A2 / 134 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS910R
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	53,00
Recommended rim size	11.00
Permitted rim size	11, 11SDC, 12, 12SDC
Maximum air pressure [bar].	3,75
Section width (mm)	334
Outer diameter of tyre [mm].	989
Stat. radius (SLR) [mm]	451
Rolling circumference [mm].	2996
Tread depth (mm)	18,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A2	2900	10	Loader dozer	3,75	
134 B	2120	50	Transport	3,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.