

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10000804 |
| Valid tyre size | 365 / 70 R 18 |
| LI / SI / PR | 146 A2 / 135 B |
| TL/TT | TL |
| Brand | Maxam |
| Tread pattern | MS910R |



Notes and features

- The Maxam MS910R is a radial tyre for wheel loaders and telescopic loaders.
- Its versatile tread offers particularly good traction on muddy surfaces.
- The reinforced sidewall protects the tyre and rim from damage.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10000804 |
| EAN | 6959655435160 |
| Valid tyre size | 365 / 70 R 18 |
| LI / SI / PR | 146 A2 / 135 B |
| TL/TT | TL |
| Brand | Maxam |
| Tread pattern | MS910R |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 55,00 |
| Recommended rim size | 11.00 |
| Permitted rim size | 12.00, 13.00 |
| Maximum air pressure [bar]. | 3,75 |
| Section width (mm) | 363 |
| Outer diameter of tyre [mm]. | 966 |
| Stat. radius (SLR) [mm] | 438 |
| Rolling circumference [mm]. | 2925 |
| Tread depth (mm) | 19,5 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 146 A2 | 3000 | 10 | Loader dozer | 3,75 | |
| 135 B | 2180 | 50 | Transport | 3,75 | |