

TYRES

Product group	Tyres	
Item number	10000805	
Valid tyre size	335 / 80 R 20	
LI / SI / PR	147 A2 / 136 B	
TL/TT	TL	
Brand	Maxam	
Tread pattern	MS910R	





Notes and features

- The Maxam MS910R is a radial tyre for wheel loaders and telescopic loaders.
- Its versatile tread offers particularly good traction on muddy surfaces.
- The reinforced sidewall protects the tyre and rim from damage.



Technical Informations

Item number	10000805
EAN	6959655435085
Valid tyre size	335 / 80 R 20
LI / SI / PR	147 A2 / 136 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS910R
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	57,00
Recommended rim size	11.00
Maximum air pressure [bar].	3,75
Section width (mm)	339
Outer diameter of tyre [mm].	1044
Stat. radius (SLR) [mm]	478
Rolling circumference [mm].	3147
Tread depth (mm)	18,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A2	3075	10	Loader dozer	3,75	
136 B	2240	50	Transport	3,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.