

## **TYRES**

Product group	Tyres
Item number	10000806
Valid tyre size	365 / 80 R 20
LI / SI / PR	153 A2 / 141 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS910R





## Notes and features

- The Maxam MS910R is a radial tyre for wheel loaders and telescopic loaders.
- Its versatile tread offers particularly good traction on muddy surfaces.
- The reinforced sidewall protects the tyre and rim from damage.



## **Technical Informations**

Item number	10000806
EAN	6959655435122
Valid tyre size	365 / 80 R 20
LI / SI / PR	153 A2 / 141 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS910R
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	67,00
Recommended rim size	11.00
Permitted rim size	11,011SDC, 12, 12SDC
Maximum air pressure [bar].	3,75
Section width (mm)	363
Outer diameter of tyre [mm].	1089
Stat. radius (SLR) [mm]	498
Rolling circumference [mm].	3300
Tread depth (mm)	18,5
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A2	3650	10	Loader dozer	3,75	
141 B	2575	50	Transport	3,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.