

TYRES

Product group	Tyres
Item number	10000807
Valid tyre size	405 / 70 R 20
LI / SI / PR	155 A2 / 143 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS910R



MAXAM

Notes and features

- The Maxam MS910R is a radial tyre for wheel loaders and telescopic loaders.
- Its versatile tread offers particularly good traction on muddy surfaces.
- The reinforced sidewall protects the tyre and rim from damage.

Technical Informations

Item number	10000807
EAN	6959655435108
Valid tyre size	405 / 70 R 20
LI / SI / PR	155 A2 / 143 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS910R
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	71,00
Recommended rim size	13.00
Permitted rim size	12, 12SDC, 13SDC
Maximum air pressure [bar].	3,75
Section width (mm)	407
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	493
Rolling circumference [mm].	3260
Tread depth (mm)	20,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A2	3875	10	Loader dozer	3,75	
143 B	2725	50	Transport	3,75	