

TYRES

Product group	Tyres
Item number	10000828
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS910R



Notes and features

- The Maxam MS910R is a radial tyre for wheel loaders and telescopic loaders.
- Its versatile tread offers particularly good traction on muddy surfaces.
- The reinforced sidewall protects the tyre and rim from damage.

Technical Informations

Item number	10000828
EAN	6959655435191
Valid tyre size	460 / 70 R 24
Alternative size 1	17.5LR24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Maxam
Tread pattern	MS910R
TRA Code	R4
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	108,00
Recommended rim size	DW15L
Permitted rim size	DW14L, DW16L
Maximum air pressure [bar].	4,00
Section width (mm)	460
Outer diameter of tyre [mm].	1249
Stat. radius (SLR) [mm]	590
Rolling circumference [mm].	3785
Tread depth (mm)	23,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40	Transport	4,00	
159 B	4375	50	Transport	4,00	
	5470	10	Loader dozer	4,00	