

TYRES

Product group	Tyres
Item number	10000862
Valid tyre size	26.5 R 29
LI / SI / PR	217 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 315



Notes and features

- The BKT Earthmax SR 315 was specially developed for loaders in the mining sector
- Due to its very good cut resistance, the tyre is extremely puncture-proof and durable
- Thanks to the L3S tread pattern, the tyre is also protected from overheating, even over longer distances
- The high lateral stability provides high ride comfort

Technical Informations

Item number	10000862
EAN	8903094070787
Valid tyre size	26.5 R 29
LI / SI / PR	217 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 315
TRA Code	L3S
Star Rating	***
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	733,74
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	8,00
Section width (mm)	725
Outer diameter of tyre [mm].	1865
Stat. radius (SLR) [mm]	830
Rolling circumference [mm].	5635
Tread depth (mm)	44,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
217 A2	23000	10	Loader dozer	8,00	