

TYRES

Product group	Tyres
Item number	10000865
Valid tyre size	500 / 60 R 22.5
LI / SI / PR	163 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M



Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.

Technical Informations

Item number	10000865
EAN	8903094069446
Valid tyre size	500 / 60 R 22.5
LI / SI / PR	163 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	109,47
Recommended rim size	AG16.00
Permitted rim size	15.00, 17.00
Maximum air pressure [bar].	6,00
Section width (mm)	503
Outer diameter of tyre [mm].	1172
Stat. radius (SLR) [mm]	544
Rolling circumference [mm].	3625
Tread depth (mm)	20,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 D	4875	65		6,00	