

## **RIMS**

Product group	Rims
Item number	10000866
Valid rim size	17.00 - 25 / 1.7
Rim connection	12/371/425
Bolt hole design	A3
Offset (mm)	+27
Rim colour	Anthrazit
Brand	Jantsa





## **Technical Informations**

Load capacity of rim 1 [kg]	6000
Speed Rims 1 [km/h]	10
Maximum speed [km/h].	10
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	129,00
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	three-part
Rim material	steel
RAL	RAL7016
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rim design industry	Standard
Rim flange height [inch]	1.7
Disc thickness [mm]	15
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	12
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	371
Bolt hole circle diameter [mm]	425
Valve seat	External Valve
Valve hole diameter [mm]	20.5
Preassembled valve	No
TPMS-kompatibles Ventil	No