

TYRES

Product group	Tyres
Item number	10000867
Valid tyre size	IF 1250 / 50 R 32 CFO
LI / SI / PR	201 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

Technical Informations

Item number	10000867
EAN	8903094070763
Valid tyre size	IF 1250 / 50 R 32 CFO
LI / SI / PR	201 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	643,52
Recommended rim size	VA44 / 1.7
Maximum air pressure [bar].	3,20
Section width (mm)	1247
Tread width (mm)	1120
Outer diameter of tyre [mm].	2063
Stat. radius (SLR) [mm]	897
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6136
Tread depth (mm)	59,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
201 B	14500	50		3,20	