

WHEELS

Product group	Wheels
Item number	10000868
Valid wheel size	400 / 50 - 15
Brand	BKT
Tread pattern	AS 504
Valid rim size	13 LB x 15 H2
Rim connection	6/161/205
Bolt hole design	E2
Offset (mm)	-85
Rim colour	Silver
Load capacity complete wheel [kg]	1400
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15710565
LI / SI / PR	109 A8 / 121 A8, 8 PR
Load capacity 1 [kg]	1030
Speed 1 [km/h].	40
Load capacity 2 [kg]	1450
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	45,85
ECE regulation number	ECE 106
Section width (mm)	395

Stat. radius (SLR) [mm]	369
Rolling circumference [mm].	2387
Tread depth (mm)	19,5
Number of lugs	14x2
E-Ready	No
Assembly Item no. Rim	• 32010326
Load capacity of rim 1 [kg]	1400
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	1400
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,00
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7

Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade