

## WHEELS

Product group	Wheels
Item number	10000870
Valid wheel size	400 / 70 R 18
Brand	Trelleborg
Tread pattern	TH400
Valid rim size	13 x 18
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	+40
Rim colour	Silver
Load capacity complete wheel [kg]	3075
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	97,15
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Bohnenkamp  
Moving Professionals

  
**TRELLEBORG**

## Technical Informations

Assembly Item no. Tyres	• 13627716
LI / SI / PR	147 A8 / 147 B
Load capacity 1 [kg]	3075
Speed 1 [km/h].	40
Load capacity 2 [kg]	3075
Speed 2 [km/h].	50
Maximum air pressure [bar].	4,00
TL/TT	TL

Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	not necessary
Section width (mm)	403
Stat. radius (SLR) [mm]	450
Rolling circumference [mm].	3040
Assembly Item no. Rim	• 33060096
Load capacity of rim 1 [kg]	3750
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3150
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig

---

Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade