

WHEELS

Product group	Wheels
Item number	10000872
Valid wheel size	500 / 70 R 24
Brand	Michelin
Tread pattern	BibLoad Hard Surface
Valid rim size	DW 15 L x 24
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	208,85
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 13375247
LI / SI / PR	164 A8 / 164 B
Load capacity 1 [kg]	5000
Speed 1 [km/h].	40
Load capacity 2 [kg]	5000
Speed 2 [km/h].	50
Maximum air pressure [bar].	4,00
TL/TT	TL

Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	not necessary
Section width (mm)	511
Stat. radius (SLR) [mm]	581
Rolling circumference [mm].	3866
Tread depth (mm)	33,0
Tyre capacity 75% [ltr.]	265
Assembly Item no. Rim	• 33060885
Load capacity of rim 1 [kg]	5750
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4850
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	12

Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade