

WHEELS

| | |
|-----------------------------------|---------------|
| Product group | Wheels |
| Item number | 10000886 |
| Valid wheel size | 400 / 50 - 15 |
| Brand | Deli |
| Tread pattern | SG-818 |
| Valid rim size | 13 LB x 15 H2 |
| Rim connection | 6/161/205 |
| Bolt hole design | E2 |
| Offset (mm) | -85 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 1400 |
| Speed complete wheel [km/h] | 40 |



Technical Informations

| | |
|-----------------------------|------------------------|
| Assembly Item no. Tyres | • 19111144 |
| LI / SI / PR | 109 A8 / 121 A8, 10 PR |
| Load capacity 1 [kg] | 1030 |
| Speed 1 [km/h]. | 40 |
| Load capacity 2 [kg] | 1450 |
| Speed 2 [km/h]. | 40 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 43,35 |
| Section width (mm) | 383 |
| Rolling circumference [mm]. | 2300 |

| | |
|--------------------------------|----------------|
| Tread depth (mm) | 17,9 |
| E-Ready | No |
| Assembly Item no. Rim | • 32010326 |
| Load capacity of rim 1 [kg] | 1400 |
| Speed Rims 1 [km/h] | 20 |
| Load capacity of rim 2 [kg] | 1400 |
| Speed Rims 2 [km/h] | 40 |
| Maximum speed [km/h]. | 40 |
| Maximum air pressure [bar]. | 3,00 |
| Hump | H2 |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 6 |
| Bolt hole diameter [mm] | 21.5 |
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |
| Valve design | Metal valve |
| Valve designation ETRTO | V5.01.1 |

| | |
|-------------------|--------|
| Valve length [mm] | 50.0 |
| Valve angle [°] | gerade |
