

WHEELS

Product group	Wheels
Item number	10000886
Valid wheel size	400 / 50 - 15
Brand	Deli
Tread pattern	SG-818
Valid rim size	13 LB x 15 H2
Rim connection	6/161/205
Bolt hole design	E2
Offset (mm)	-85
Rim colour	Silver
Load capacity complete wheel [kg]	1400
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	43,35
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Deli Tire
ROAD SYMBIOSIS

Technical Informations

Assembly Item no. Tyres	• 19111144
LI / SI / PR	109 A8 / 121 A8, 10 PR
Load capacity 1 [kg]	1030
Speed 1 [km/h].	40
Load capacity 2 [kg]	1450
Speed 2 [km/h].	40
Maximum air pressure [bar].	3,00
TL/TT	TL

Tyre colour	Black
E-Ready	No
Antistatic	No
Section width (mm)	383
Rolling circumference [mm].	2300
Tread depth (mm)	17,9
Assembly Item no. Rim	• 32010326
Load capacity of rim 1 [kg]	1400
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	1400
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	H2
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038

Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade