

## WHEELS

Product group	Wheels
Item number	10000894
Valid wheel size	10.0 / 75 - 15.3
Brand	BKT
Tread pattern	MP 567
Valid rim size	9.00 x 15.3
Rim connection	5/66.5/112
Bolt hole design	A1
Rim colour	Silver
Load capacity complete wheel [kg]	1550
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15711723
LI / SI / PR	111 A8 / 123 A8, 10 PR
Load capacity 1 [kg]	1090
Speed 1 [km/h].	40
Load capacity 2 [kg]	1550
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	37,48
ECE regulation number	ECE 106

Section width (mm)	258
Stat. radius (SLR) [mm]	355
Rolling circumference [mm].	2310
Tread depth (mm)	21,5
Number of lugs	18x2
E-Ready	No
Assembly Item no. Rim	• 32010020
Load capacity of rim 1 [kg]	2180
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2060
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,90
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
hub hole diameter [mm].	66.5
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

---

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade