

TYRES

Product group	Tyres
Item number	10000895
Valid tyre size	17.5 R 25
LI / SI / PR	188 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 55



Notes and features

- The BKT Earthmax SR 55 was specially developed for loaders in mining and recycling applications
- Due to its very good cut resistance and the extra deep L5 tread pattern, the tyre is extremely puncture-proof and durable
- The high lateral stability provides high ride comfort

Technical Informations

Item number	10000895
EAN	8903094069941
Valid tyre size	17.5 R 25
LI / SI / PR	188 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 55
TRA Code	L5S
Star Rating	***
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	309,30
Recommended rim size	14.00/1.5
Maximum air pressure [bar].	8,00
Section width (mm)	453
Outer diameter of tyre [mm].	1399
Stat. radius (SLR) [mm]	630
Rolling circumference [mm].	4211
Tread depth (mm)	68,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
188 A2	10000	10	Loader dozer	8,00	