

TYRES

Product group	Tyres
Item number	10000901
Valid tyre size	900 / 55 R 38
LI / SI / PR	181 A8 / 179 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657



Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.

Technical Informations

Item number	10000901
EAN	8903094067534
Valid tyre size	900 / 55 R 38
LI / SI / PR	181 A8 / 179 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	380,20
Recommended rim size	DW27B
Permitted rim size	DW30B
Maximum air pressure [bar].	2,80
Section width (mm)	880
Tread width (mm)	840
Outer diameter of tyre [mm].	1950
Stat. radius (SLR) [mm]	880
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5842
Contact area [cm²]	3720
Tread depth (mm)	61,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		2,80	
179 D	7750	65			