

## WHEELS

|                                   |                |
|-----------------------------------|----------------|
| Product group                     | Wheels         |
| Item number                       | 10000905       |
| Valid wheel size                  | 15.0 / 55 - 17 |
| Brand                             | BKT            |
| Tread pattern                     | AS 504         |
| Valid rim size                    | 13.00 x 17     |
| Rim connection                    | 6/161/205      |
| Bolt hole design                  | B2             |
| Offset (mm)                       | +45            |
| Rim colour                        | Silver         |
| Load capacity complete wheel [kg] | 2120           |
| Speed complete wheel [km/h]       | 40             |



## Technical Informations

|                            |                        |
|----------------------------|------------------------|
| Assembly Item no. Tyres    | • 15711860             |
| LI / SI / PR               | 122 A8 / 134 A8, 10 PR |
| Load capacity 1 [kg]       | 1500                   |
| Speed 1 [km/h].            | 40                     |
| Load capacity 2 [kg]       | 2120                   |
| Speed 2 [km/h].            | 40                     |
| Antistatic                 | No                     |
| Tyre colour                | Black                  |
| Nettogewicht [kg] (gültig) | 64,93                  |
| ECE regulation number      | ECE 106                |
| Section width (mm)         | 380                    |

|                             |                               |
|-----------------------------|-------------------------------|
| Stat. radius (SLR) [mm]     | 395                           |
| Rolling circumference [mm]. | 2608                          |
| Tread depth (mm)            | 23,0                          |
| Number of lugs              | 17x2                          |
| E-Ready                     | No                            |
| Assembly Item no. Rim       | • 33060077                    |
| Load capacity of rim 1 [kg] | 4150                          |
| Speed Rims 1 [km/h]         | 40                            |
| Load capacity of rim 2 [kg] | 3050                          |
| Speed Rims 2 [km/h]         | 65                            |
| Maximum speed [km/h].       | 40                            |
| Maximum air pressure [bar]. | 2,60                          |
| Type of drive               | Angetriebene & gezogene Achse |
| Hump                        | kein Hump                     |
| Valve protection            | VS H                          |
| Single / multi-part         | einteilig                     |
| Rim material                | steel                         |
| RAL                         | RAL9006                       |
| Cavity Sealed               | No                            |
| Ventilation holes           | No                            |
| Verschweißung beidseitig    | No                            |
| Rim centering               | BC                            |
| Number of bolt holes        | 6                             |
| Bolt hole diameter [mm]     | 21.5                          |
| Countersinking              | Sphere                        |
| Spherical countersink [mm]. | R16                           |
| hub hole diameter [mm].     | 161                           |

---

|                                       |                |
|---------------------------------------|----------------|
| <b>Bolt hole circle diameter [mm]</b> | 205            |
| <b>Valve seat</b>                     | External Valve |
| <b>Valve hole diameter [mm]</b>       | 15.7           |
| <b>Preassembled valve</b>             | No             |
| <b>Valve design</b>                   | Metal valve    |
| <b>Valve designation ETRTO</b>        | V5.01.1        |
| <b>Valve length [mm]</b>              | 50.0           |
| <b>Valve angle [°]</b>                | gerade         |