

## TYRES

|                 |                    |
|-----------------|--------------------|
| Product group   | Tyres              |
| Item number     | 10000906           |
| Valid tyre size | 315 / 80 R 22.5    |
| LI / SI / PR    | 157 / 154 L, 20 PR |
| TL/TT           | TL                 |
| Brand           | GoodTrip           |
| Tread pattern   | GMD30              |



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The GoodTrip GMD30 is a truck tyre for the drive axle for construction site vehicles.
- The tread pattern with pronounced blocks and grooves ensures very good driving and braking performance.
- The open tyre shoulder prevents the tyre from overheating.
- Its special tread compound and high tread depth make the tyre particularly durable.

## Technical Informations

|                              |                    |
|------------------------------|--------------------|
| Item number                  | 10000906           |
| EAN                          | 8859625700152      |
| Valid tyre size              | 315 / 80 R 22.5    |
| LI / SI / PR                 | 157 / 154 L, 20 PR |
| TL/TT                        | TL                 |
| Brand                        | GoodTrip           |
| Tread pattern                | GMD30              |
| M+S                          | M+S                |
| 3PMSF                        | 3PMSF              |
| Axle position truck          | RA                 |
| Rolling resistance           | D                  |
| Wet grip                     | B                  |
| Rolling noise [db].          | 73                 |
| Rolling noise level          | B                  |
| Antistatic                   | No                 |
| Tyre colour                  | Black              |
| ECE regulation number        | ECE 117,ECE 54     |
| Nettogewicht [kg] (gültig)   | 65,38              |
| Recommended rim size         | 9.00               |
| Permitted rim size           | 9.75               |
| Maximum air pressure [bar].  | 8,30               |
| Section width (mm)           | 312                |
| Tread width (mm)             | 262                |
| Outer diameter of tyre [mm]. | 1076               |
| Stat. radius (SLR) [mm]      | 500                |
| Rolling circumference [mm].  | 3401               |

---

|                  |      |
|------------------|------|
| Tread depth (mm) | 20,5 |
| E-Ready          | No   |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 157 L | 4125               | 120          | Single        | 8,30                     |              |
| 154 L | 3750               | 120          | Twin          | 8,30                     |              |