

TYRES

Product group	Tyres
Item number	10000907
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	157 / 154 L, 20 PR
TL/TT	TL
Brand	GoodTrip
Tread pattern	GHA20



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The GoodTrip GHA20 is a radial truck tyre for the front or trailer axle for use in regional and long-distance transport.
- Its large contact area and angular tyre shoulder ensure very good driving stability and slow wear.
- The four wide circumferential grooves ensure excellent water drainage.
- Stone ejectors prevent tyre damage caused when small stones penetrate the tread.

Technical Informations

Item number	10000907
EAN	8859625700091
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	157 / 154 L, 20 PR
TL/TT	TL
Brand	GoodTrip
Tread pattern	GHA20
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	C
Wet grip	B
Rolling noise [db].	70
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	61,73
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,30
Section width (mm)	312
Tread width (mm)	240
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3363

Tread depth (mm)	14,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 L	4125	120	Single	8,30	
154 L	3750	120	Twin	8,30	