

TYRES

Product group	Tyres
Item number	10000922
Valid tyre size	480 / 70 R 34
LI / SI / PR	158 A8 / 155 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor



Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.

Technical Informations

Item number	10000922
EAN	8903094071036
Valid tyre size	480 / 70 R 34
LI / SI / PR	158 A8 / 155 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	140,65
Recommended rim size	W15L
Permitted rim size	W14L, W16L
Maximum air pressure [bar].	3,20
Section width (mm)	479
Tread width (mm)	454
Outer diameter of tyre [mm].	1580
Stat. radius (SLR) [mm]	729
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4761
Tread depth (mm)	49,0
Number of lugs	23x2
E-Ready	Yes

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		3,20	
155 D	3875	65		3,20	