

TYRES

Product group	Tyres
Item number	10000923
Valid tyre size	480 / 70 R 38
LI / SI / PR	148 A8 / 145 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.

Technical Informations

Item number	10000923
EAN	8903094071043
Valid tyre size	480 / 70 R 38
LI / SI / PR	148 A8 / 145 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor
Carcass properties	E-Ready
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	144,38
Recommended rim size	W15L
Permitted rim size	W14L, W16L
Maximum air pressure [bar].	1,60
Section width (mm)	479
Tread width (mm)	454
Outer diameter of tyre [mm].	1681
Stat. radius (SLR) [mm]	758
Speed Radius Index (SRI)	800
Rolling circumference [mm].	5000
Tread depth (mm)	49,0
Number of lugs	24x2
E-Ready	Yes

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A8	3150	40		1,60	
145 D	2900	65		1,60	