

## TYRES

Product group	Tyres
Item number	10000927
Valid tyre size	28 L - 26
LI / SI / PR	160 A6 / 157 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 390



## Notes and features

- Industrial bias tyre with block tread pattern for varying uses, e.g. road construction on drum compactors, on industrial tractors or in agriculture and landscape management on different machines and heavy equipment.
- Wide tread pattern block and rounded shoulders guarantee optimal soil protection and good surface contact for good propulsion.
- Increased tread pattern depth and reinforced casing for a longer service life.

## Technical Informations

Item number	10000927
EAN	8903094070695
Valid tyre size	28 L - 26
LI / SI / PR	160 A6 / 157 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 390
Carcass properties	Dual Bead
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	184,70
Recommended rim size	DW25B
Permitted rim size	DW23B
Maximum air pressure [bar].	1,90
Section width (mm)	714
Outer diameter of tyre [mm].	1560
Stat. radius (SLR) [mm]	690
Rolling circumference [mm].	4545
Tread depth (mm)	27,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A6	4500	30		1,90	
157 A8	4125	40		1,90	