

WHEELS

Product group	Wheels
Item number	10000933
Valid wheel size	425 / 55 R 17
Brand	BKT
Tread pattern	Ridemax FL 693 M
Valid rim size	13.00 x 17
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+45
Rim colour	Silver
Load capacity complete wheel [kg]	2500
Speed complete wheel [km/h]	65
Nettogewicht [kg] (gültig)	78,99
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15717218
LI / SI / PR	140 A8 / 129 D
Load capacity 1 [kg]	2500
Speed 1 [km/h].	40
Load capacity 2 [kg]	1850
Speed 2 [km/h].	65
Maximum air pressure [bar].	4,00
TL/TT	TL

Tyre colour	Black
E-Ready	No
Carcass properties	Steel Belted
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	420
Stat. radius (SLR) [mm]	397
Rolling circumference [mm].	2704
Tread depth (mm)	14,5
Number of lugs	14x2
Assembly Item no. Rim	• 33060077
Load capacity of rim 1 [kg]	4150
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3050
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 DS 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006

Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade