

## WHEELS

Product group	Wheels
Item number	10000938
Valid wheel size	28 L - 26
Brand	BKT
Tread pattern	TR 390
Valid rim size	DW 25 B x 26
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-100
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	30
Nettogewicht [kg] (gültig)	280,85
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 10000927
LI / SI / PR	160 A6 / 157 A8, 16 PR
Load capacity 1 [kg]	4500
Speed 1 [km/h].	30
Load capacity 2 [kg]	4125
Speed 2 [km/h].	40
Maximum air pressure [bar].	1,90
TL/TT	TL

Tyre colour	Black
E-Ready	No
Carcass properties	Dual Bead
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	714
Stat. radius (SLR) [mm]	690
Rolling circumference [mm].	4545
Tread depth (mm)	27,0
Assembly Item no. Rim	• 32010445
Load capacity of rim 1 [kg]	9660
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7100
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve

Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No
Verschweißung beidseitig	No
Number of additional holes	6
Additional pitch circle diameter [mm].	430
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade