

WHEELS

Product group	Wheels
Item number	10000939
Valid wheel size	31 x 15.5 - 15
Brand	BKT
Tread pattern	Skid Power HD
Valid rim size	13 x 15
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+45
Rim colour	Silver
Load capacity complete wheel [kg]	1650
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	55,29
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15772094
LI / SI / PR	125 A8, 10 PR
Load capacity 1 [kg]	1650
Speed 1 [km/h].	40
Maximum air pressure [bar].	4,20
TL/TT	TL
Tyre colour	Black
E-Ready	No

Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	400
Stat. radius (SLR) [mm]	378
Speed Radius Index (SRI)	550
Rolling circumference [mm].	2411
Tread depth (mm)	21,0
Assembly Item no. Rim	• 10000694
Load capacity of rim 1 [kg]	2800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2500
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	40
Type of drive	Towed axle
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 DS 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	8.0
Ventilation holes	No

Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade