

TYRES

Product group	Tyres	
Item number	10000946	
Valid tyre size	560 / 60 R 22.5	
LI / SI / PR	169 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	590	





Notes and features

- The Alliance 590 is a flotation radial tyre for use in agriculture and on construction sites.
- Its robust steel belt construction (Steel Belted) and the cut and tear resistant rubber compound enable high load capacities.
- The tyre is ideal for use in the field as well as for on- and off-road applications.



Technical Informations

Item number	10000946
EAN	8903635046721
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	169 D
TL/TT	TL
Brand	Alliance
Tread pattern	590
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	134,00
Recommended rim size	AG16.00
Maximum air pressure [bar].	6,00
Section width (mm)	550
Outer diameter of tyre [mm].	1244
Stat. radius (SLR) [mm]	563
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3775
Contact area [cm²]	1560
Tread depth (mm)	23,0
Number of lugs	30x2
Tyre capacity 75% [Itr.]	269.77
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Inde	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 [5800	65	Free Rolling	6,00	