

## **TYRES**

Product group	Tyres	
Item number	10000949	
Valid tyre size	10.0 / 75 - 15.3	
LI / SI / PR	127 A6, 10 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	AT 621 (Industrial)	



## Notes and features

- Excellent traction in difficult terrain.
- Wide tread blocks increase puncture resistance.
- Good mileage through the use of a wear and cut-resistant rubber compound
- For use on backhoe loaders, wheel loaders and similar vehicles.



## **Technical Informations**

Item number	10000949
EAN	8903094070619
Valid tyre size	10.0 / 75 - 15.3
LI / SI / PR	127 A6, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 621 (Industrial)
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	22,21
Recommended rim size	9.0
Maximum air pressure [bar].	5,25
Section width (mm)	267
Outer diameter of tyre [mm].	780
Stat. radius (SLR) [mm]	373
Speed Radius Index (SRI)	575
Rolling circumference [mm].	2385
Tread depth (mm)	16,5
Number of lugs	26x2
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 A6	1750	30		5,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.