

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 10000955 |
| Valid tyre size | 650 / 55 R 26.5 |
| LI / SI / PR | 177 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 590 |



Notes and features

- The Alliance 590 is a flotation radial tyre for use in agriculture and on construction sites.
- Its robust steel belt construction (Steel Belted) and the cut and tear resistant rubber compound enable high load capacities.
- The tyre is ideal for use in the field as well as for on- and off-road applications.

Technical Informations

| | |
|---------------------------------|----------------------|
| Item number | 10000955 |
| EAN | 8903635047179 |
| Valid tyre size | 650 / 55 R 26.5 |
| LI / SI / PR | 177 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 590 |
| Carcass properties | Steel Belted,HD,C.R. |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 187,20 |
| Recommended rim size | AG20.00 |
| Maximum air pressure [bar]. | 6,00 |
| Section width (mm) | 650 |
| Outer diameter of tyre [mm]. | 1390 |
| Stat. radius (SLR) [mm] | 635 |
| Speed Radius Index (SRI) | 675 |
| Rolling circumference [mm]. | 4253 |
| Contact area [cm ²] | 1999 |
| Tread depth (mm) | 27,0 |
| Number of lugs | 14x2 |
| Tyre capacity 75% [ltr.] | 391.42 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 177 D | 7300 | 65 | | 6,00 | |